

A better environment inside and out.™

Solar Gard® TrueVue™

For a clear view day or night



Solar Gard® TrueVue™ window film provides optimum clarity for stunning exterior views day and night.

TrueVue offers you:

- Protection from the sun's damaging ultraviolet rays
- Rejects up to 82% of the total solar energy to increase your comfort
- Reduces both the cost of air conditioning and your carbon footprint
- Controls hot spots and uneven temperature zones
- Reduces glare by up to 94%
- Helps to increase your interior daytime privacy

TrueVue comes in four different shades, 5, 15, 30 and 40:

- Provides you with a choice in visual appearance and solar performance

TrueVue is made by one of the world's leading window film manufacturers in quality and performance.

It comes with a limited lifetime residential or a 10 year commercial warranty.



TrueVue features and benefits:

Low internal and external reflection

- Provides you with superior external views day or night

Solar heat protection

- Decreases energy costs by reducing the need for air conditioning
- Improves comfort
- Reduces hotspots

Warm rich tone

- Significantly reduces glare
- Gives glass a pleasing neutral appearance

Blocks up to 99% of UV

- Protects expensive artwork, precious antiques, retail merchandise, carpets, flooring and furniture from damaging UV rays
- Protects against premature aging and skin cancer

Limited lifetime residential and 10 year commercial warranty

- Guarantees you a minimum length of service



Performance measurements*

	Solar energy transmittance (%)	Total solar energy absorptance (%)	Solar energy reflectance (%)	Visible light transmittance (%)	Visible light reflectance exterior (%)	Visible light reflectance interior (%)	Emissivity	Winter u-factor (Btu hr/ft ² °F)	Shading coefficient	Solar heat gain coefficient	Solar selectivity index - luminous efficacy (MLT/SC)	Light to solar heat gain factor (MLT/SHGC)	Ultraviolet blocked (%) (300 to 380 nanometers)	Total solar energy rejected (%)	Solar heat gain reduction (%)	Glare reduction (%)
TrueVue™ 40	38	40	22	39	14	10	.75	.99	.57	.49	.69	.80	>99	51	43	56
TrueVue™ 30	27	41	32	31	22	13	.75	.99	.45	.39	.70	.81	>99	61	55	65
TrueVue™ 15	9	40	51	12	45	23	.75	.99	.24	.20	.51	.60	>99	80	76	87
TrueVue™ 5	6	43	51	5	45	8	.75	.99	.21	.18	.25	.29	>99	82	79	94

* Performance results were obtained through measurements on the inside of 3mm (1/8") thick clear glass and were then calculated using NFRC methodology and LBNL Window 5.2 software, and are subject to variations within industry standards and only intended for estimating purposes.

www.solargard.com.au

Saint-Gobain Performance Plastics
 1/6 Stanton Road, Seven Hills NSW 2147
 Australia
 Tel: 61 2 9838 8888

PDF0165TVCAU 02/12
 © Copyright 2012, Saint-Gobain Performance Plastics Corporation and/or its affiliates
 All Rights Reserved • www.solargard.com

Please recycle

